

# Deadlock



**Concepts:** system **deadlock:** no further progress  
four necessary & sufficient conditions

**Models:** deadlock - no eligible actions


**Practice:** blocked threads

**Aim:** deadlock avoidance - to design systems where deadlock cannot occur.

### Deadlock: four necessary and sufficient conditions

- ◆ **Serially reusable resources:**  
the processes involved share resources which they use under *mutual exclusion*.
- ◆ **Incremental acquisition:**  
processes hold on to resources already allocated to them while waiting to acquire additional resources.
- ◆ **No pre-emption:**  
once acquired by a process, resources cannot be pre-empted (forcibly withdrawn) but are only released voluntarily.
- ◆ **Wait-for cycle:**  
a circular chain (or cycle) of processes exists such that each process holds a resource which its successor in the cycle is waiting to acquire.

### Wait-for cycle






## Dining Philosophers - model structure diagram

Each FORK is a **shared resource** with actions **get** and **put**.

When hungry, each PHIL must first get his right and left forks before he can start eating.



9

©Magee/Kramer 2<sup>nd</sup> Edition

2015 Concurrency: Deadlock

## Dining Philosophers - model

```

FORK = (get -> put -> FORK) .
PHIL = (sitdown ->right.get->left.get
        ->eat ->right.put->left.put
        ->arise->PHIL) .
    
```

Table of philosophers:

```

| | DINERS (N=5) = forall [i:0..N-1]
  (phil[i]:PHIL | |
   {phil[i].left,phil[ (i-1)+N ] .right } : : FORK
  ) .
    
```

**Can this system deadlock?**

10

©Magee/Kramer 2<sup>nd</sup> Edition

2015 Concurrency: Deadlock

## Dining Philosophers - model analysis

```

Trace to DEADLOCK:
phil.0.sitdown
phil.0.right.get
phil.1.sitdown
phil.1.right.get
phil.2.sitdown
phil.2.right.get
phil.3.sitdown
phil.3.right.get
phil.4.sitdown
phil.4.right.get
    
```

This is the situation where all the philosophers become hungry at the same time, sit down at the table and each philosopher picks up the fork to his **right**.

The system can make no further progress since each philosopher is waiting for a fork held by his neighbour i.e. a **wait-for cycle** exists!

11


©Magee/Kramer 2<sup>nd</sup> Edition

2015 Concurrency: Deadlock

## Dining Philosophers

Deadlock is easily detected in our **model**.

How easy is it to detect a potential deadlock in an **implementation**?




12

©Magee/Kramer 2<sup>nd</sup> Edition

2015 Concurrency: Deadlock

## Dining Philosophers - implementation in Java



## Dining Philosophers - Fork monitor

```
class Fork {
    private boolean taken=false;
    private PhilCanvas display;
    private int identity;

    Fork(PhilCanvas disp, int id)
    { display = disp; identity = id;}

    synchronized void put() {
        taken=false;
        display.setFork(identity,taken);
        notify();
    }

    synchronized void get()
        throws java.lang.InterruptedException {
        while (taken) wait();
        taken=true;
        display.setFork(identity,taken);
    }
}
```

taken  
encodes the  
state of the  
fork

## Dining Philosophers - Philosopher implementation

```
class Philosopher extends Thread {
    ...
    public void run() {
        try {
            while (true) {
                view.setPhil(identity,view.THINKING);
                sleep(controller.sleepTime()); // hungry
                view.setPhil(identity,view.HUNGRY);
                right.get(); // gotright chopstick
                view.setPhil(identity,view.GOTRIGHT);
                sleep(500);
                left.get(); // eating
                view.setPhil(identity,view.EATING);
                sleep(controller.eatTime());
                right.put();
                left.put();
            }
        } catch (java.lang.InterruptedException e){}
    }
}
```

Follows from the model (sitting down and leaving the table have been omitted).

## Dining Philosophers - implementation in Java


Code to create the philosopher threads and fork monitors:

```
for (int i =0; i<N; ++i)
    fork[i] = new Fork(display,i);
for (int i =0; i<N; ++i){
    phil[i] =
        new Philosopher
            (this,i,fork[(i-1+N)%N],fork[i]);
    phil[i].start();
}
```

## Dining Philosophers

To ensure deadlock occurs eventually, the slider control may be moved to the left. This reduces the time each philosopher spends thinking and eating.

This "speedup" increases the probability of deadlock occurring.



## Deadlock-free Philosophers

Deadlock can be avoided by ensuring that a wait-for cycle cannot exist. **How?**

Introduce an *asymmetry* into our definition of philosophers.


Use the identity *I* of a philosopher to make **even** numbered philosophers get their **left** forks first, **odd** their **right** first.

**Other strategies?**

```
PHIL (I=0)
= (when (I%2==0) sitdown
  ->left.get->right.get
  ->eat
  ->left.put->right.put
  ->arise->PHIL
 |when (I%2==1) sitdown
  ->right.get->left.get
  ->eat
  ->left.put->right.put
  ->arise->PHIL
).
```

## Maze example - shortest path to "deadlock"

We can exploit the shortest path trace produced by the deadlock detection mechanism of **LTSA** to find the **shortest** path out of a **maze** to the **STOP** process!



We first model the **MAZE**.


Each position is modelled by the moves that it permits. The **MAZE** parameter gives the starting position.

eg. `MAZE (Start=8) = P[Start],  
P[0] = (north->STOP|east->P[1]),...`

## Maze example - shortest path to "deadlock"

`||GETOUT = MAZE (7) .`

Shortest path escape trace from position 7?



Trace to **DEADLOCK:**


**east**  
**north**  
**north**  
**west**  
**west**  
**north**

## Summary

---

### ◆ Concepts

- **deadlock: no further progress**
- **four necessary and sufficient conditions:**
  - ◆ **serially reusable resources**
  - ◆ **incremental acquisition**
  - ◆ **no preemption**
  - ◆ **wait-for cycle**



**Aim: deadlock avoidance**  
- to design systems where  
deadlock cannot occur.

### ◆ Models

- **no eligible actions (analysis gives shortest path trace)**

### ◆ Practice

- **blocked threads**